



# PRISTA® MVR MULTI

## CHANISAW OIL

### Description and Application

**PRISTA® MVR MULTI** chainsaw chain oil is designated for the lubrication of the chains of chainsaws. Additive package imparting very good adhesion to the cutting tool providing reduced tool wear and lower oil consumption.

**PRISTA® MVR MULTI** is formulated from highly refined base stocks and special antiwear, anticorrosion additives and tackiness agent.

### Benefits

- Better low temperature properties allowing year-round use
- Very good adhesion
- Protection against wear and rust
- Lower oil consumption

### Specifications

ISO 3448	VG 125
ISO 6743/1	ISO-L-AB

### Typical Characteristics

Parameter	Test Method	Typical Value
Appearance	Visual	Clear, brown liquid
Colour	ISO 2049	L 4.0
Density at 20°C, g/ml	EN ISO 3675	0.890
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s	EN ISO 3104	120
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s	EN ISO 3104	15
Viscosity Index	ISO 2909	130
Flash point COC, °C	EN ISO 2592	242
Pour point, °C	ISO 3016	-24

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

### Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit: [www.prista-oil.com](http://www.prista-oil.com)

### Packages

210L, 1000l, Bulk