



# PRISTA® 2T MIX

## TWO-CYCLE GASOLINE ENGINE OILS

### Description and Application

**Prista® 2T Mix** is low-ash mineral oil intended for “premix” lubrication of conventional two-cycle, air-cooled gasoline engines in passenger cars, motorcycles, motorbikes, mopeds, motocultivators, chainsaws etc.  
The recommended Oil -to-Fuel Ratio is 1:50 (or other ratio recommended by the equipment manufacturer).

### Benefits

- Good lubricating properties
- Good detergent properties
- Low power losses at start-up
- A low smoke tendency
- Provides for clean and in good condition exhaust port

### Specifications

|      | <b>Prista® 2T Mix</b> |
|------|-----------------------|
| ISO  | L-EGB                 |
| JASO | FC                    |
| API  | TC                    |

### Typical Characteristics

| <b>Parameter</b>                                | <b>Test Method</b> | <b>Typical Value</b> |
|---|--------------------|----------------------|
| Density at 20°C, g/ml                           | EN ISO 3675        | 0.880                |
| Kinematic Viscosity at 40°C, mm <sup>2</sup> /s | EN ISO 3104        | 78                   |
| Flash point COC, °C                             | EN ISO 2592        | 200                  |
| Pour point, °C                                  | ISO 3016           | -15                  |
| TBN (HClO <sub>4</sub> ), mg KOH/g              | ASTM D 2896        | 1.0                  |

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

### Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit: [www.prista-oil.com](http://www.prista-oil.com)

### Packages

1L, 210L, 1000L