



PRISTA® EMULSIN EXTRA

METALWORKING FLUIDS

Description and Application

Prista® Emulsin Extra is water-miscible metal working fluid, which is formulated with base oils of low aromatic contents and neutralised products of boric acid, anionic and non-ionic emulsifiers as well as yellow metals rust & corrosion inhibitors. This product contains amines but is free from lactic acid.

Prista® Emulsin Extra is universal, water-miscible cutting fluid for all chip-removal metalworking operations and is especially recommended for preparation of working solutions with water of hardness 7-30°dH.

Benefits

- Produces stable tight emulsions with excellent wetting properties in waters of different hardness up to 60°dH (1080 ppm)
- Ensures superior cutting tool cooling and detergency
- Suitable for machining of cast iron, steel and aluminium alloys
- Designed for use at wide concentration ranges from 4% to 15%
- Ensures long life of the emulsion by protecting the emulsion system from bacteria and fungi.

Use and applicable operations

	Water-Miscible MWF
Cast iron	Very suitable
Steel	Extremely suitable
Yellow metals	Suitable with some limitations
Aluminium	Suitable
Grinding	Suitable
Cutting	Suitable
Forming	Not suitable
Additional properties: lubricity/ EP	None

Refractive index – 1.1% per °Brix

Specifications

	Water-Miscible MWF
ISO 6743/7	ISO-L-MAE

Typical Characteristics

Parameter	Test Method	Typical Value
Properties of the concentrate: - Appearance - Kinematic Viscosity at 20°C, cSt - Density at 20°C, g/ml - Mineral oil content, %	Visual EN ISO 3104 EN ISO 3675 -	Clear brown fluid 130 0.987 42
Properties of water solutions: - pH (at 4 %) - pH (at 10 %) - Corrosion protection (Herbert test at 3%) - Corrosion protection (chip/filter paper test at 4%)	ISO 4316 ISO 4316 DIN 51360/I DIN 51360/II	9.1 9.4 R0/S0 - no corrosion 0/0 - no corrosion

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

Health, Safety and Handling



Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit: www.prista-oil.com

Fluid must be stored in closed and dry warehouses. The concentrate will stay stable if stored at temperatures from 10°C to 25°C for up to 12 months. After opening keep the container with concentrate tightly closed.

Packages

20L, 206 kg