



# PRISTA® LIMO

## GREASES

### Description and Application

The multipurpose antifriction greases **Prista® LiMo** are manufactured by thickening an appropriate mineral base oil with lithium 12-hydroxystearate soap and the addition of a proper additive package and 3% highly dispersive molybdenum disulphide (MoS<sub>2</sub>) with particle sizes of 0.65 to 0.75 µm.

These greases are used in applications calling for adequate protection against high and shock loads for the friction assemblies in construction and mining industries and in agriculture. The applications include: plain and rolling bearings, bearing bushes, roller conveyors, constant velocity joints (CV-joints), springs, heavily loaded chain and gear drives, etc.

The operating temperature range of **Prista® LiMo** greases is from -20°C to +120°C.

### Benefits

- very good adhesion properties
- improved EP properties and extra measure of protection in shock loading situations
- high roll stability and retain their consistency in heavy duty operations
- not corrosive to non-ferrous metals and steel
- water washout resistance
- adequate protection against rust formation

### Specifications

NLGI	2	3
ISO 6743/9	ISO-L-XCCHB 2(3)	
DIN 51502	KPF 2(3) K-20	

### Typical Characteristics

Parameter	Test Method	Typical Value	
		NLGI 2	NLGI 3
Oil type		mineral	
Thickener		lithium soap	
MoS <sub>2</sub> content, %	DIN 51831-1	3	
Color	Visual	Dark grey	
Kinematic Viscosity of base oil at 40°C, mm <sup>2</sup> /s	EN ISO 3104	100	
Cone Penetration, worked at 25°C, 0.1 mm	ISO 2137	280	240
Dropping Point, °C	ISO 2176	190	200
Oil Separation - separated oil at 40°C, 42h, %	IP 121	< 3	
Dynamic Rust Test (EMCOR) in distilled water	ISO 11007	0/0	
Four Ball EP Wear Test - Weld Point, N	ASTM D 2596	3150	

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

### Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit: [www.prista-oil.com](http://www.prista-oil.com)

Prista Oil Holding EAD  
www.prista-oil.com



## Packages

0.4 kg, 0.8 kg, 4 kg, 15 kg, 180 kg