



PRISTA® SHPD LS 15W-40

Old name: Prista Super SHPD

ULTRA HIGH-PERFORMANCE DIESEL ENGINE OIL

Description and Application

Prista® SHPD LS 15W-40 is a new category engine oil of medium SAPS level intended for moderately extended oil drain intervals. This oil is based on API Group II base oils as per the new motor oil tendencies and complies with the requirements imposed by the heavy-duty diesel engines running on bio-diesel fuel in accordance with EU regulations. This lubricant is designated for the lubrication of the most modern heavy duty and heavy-loaded diesel engines used in international haulage and equipped with the modern aftertreatment systems (EGR or SCR) for hazardous NOx reduction and/or diesel particulate filters (DPF) combined with low-sulfur diesel fuels.

Prista® SHPD LS 15W-40 multigrade engine oil is recommended for highly rated diesel engines complying with Euro IV, Euro V & Euro VI low emission standards and operated under severe loads and conditions.

Benefits

- Protection against cylinder bore polishing and wear
- High engine cleanliness with considerably extended drain intervals up to 60 000 km
- Problem-free operation even in case of a heavily sooted oil
- High temperature thickening protection
- Bearing corrosion protection
- Foam control
- Easy engine start-ups even at very low sub-zero temperatures

Specifications

	SAE 15W-40
ACEA	E6/E7/E9/E11
API	CK-4
Daimler Truck	DTFR 15C100
MB-old specification	228.31
MAN	M 3775
MTU	Type 3.1
Volvo	VDS-4.5
Renault Trucks	RLD-3
Deutz	DQC III-18-LA
Caterpillar	ECF-3
Cummins	CES 20086
Mack	EOS-4.5
Detroit Diesel	93K222
JASO	DH-2

Typical Characteristics

Parameter	Test Method	Typical Value
Density at 20°C, g/ml	EN ISO 3675	0.882
Kinematic Viscosity at 100°C, mm ² /s	EN ISO 3104	14.8
Kinematic Viscosity at 40°C, mm ² /s	EN ISO 3104	109
Viscosity Index	ISO 2909	140
Flash point COC, °C	EN ISO 2592	234
Pour point, °C	ISO 3016	-33
TBN (HClO ₄), mg KOH/g	ASTM D 2896	9.5
Sulfated Ash, %	EN ISO 3987	1.0

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.



Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application. For more information about product MSDS, terms and conditions for storage and shelf life please visit: www.prista-oil.com