



# PRISTA® T

## MONOGRADE AUTOMOTIVE GEAR OILS

### Description and Application

**Prista® T** monograde automotive gear oils are formulated with a special selection of high quality solvent refined and hydrotreated base stocks and an additive package to impart the appropriate anti-wear, anti-seizure and antifoam properties, and oxidation resistance.

These gear oils are developed to lubricate relatively light-duty worm gear drives and spiral bevel final drives, operating at moderate loads and sliding velocities.

**Prista® T** monograde automotive gear oils can be used in some truck manual transmissions, too, where API GL-1 and GL-2 performance level lubricants are specified.

### Benefits

- Good anti-wear and anti-seizure properties
- Very good thermal and oxidation stability
- Very good rust and corrosion protection
- Good seal compatibility

### Specifications

	SAE 90	SAE 140
API	GL-2	

### Typical Characteristics

Parameter	Test Method	Typical Value	
		SAE 90	SAE 140
Density at 20°C, g/ml	EN ISO 3675	0.893	0.902
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s	EN ISO 3104	19.3	30.0
Viscosity Index	ISO 2909	92	90
Flash point COC, °C	EN ISO 2592	268	280
Pour point, °C	ISO 3016	-15	-9
Copper Strip Corrosion, rating	EN ISO 2160	1a	
FZG Test - Failure Load Stage	ASTM D 5182	8	

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

### Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit: [www.prista-oil.com](http://www.prista-oil.com)

### Packages

20L, 210L, 1000L