



PRISTA® ULTRA C5 0W-20

HIGH PERFORMANCE PASSENGER CAR ENGINE OILS

Description and Application

Prista® Ultra C5 0W-20 is a full synthetic lubricant based on carefully selected very high quality base oils, specially developed for the gasoline and diesel direct injection Volvo Engine Architecture (VEA) engines. This product is also usable for other OEM's passenger cars requiring this viscosity grade and ACEA C5 and API SN/CF performance.

Benefits

- High oxidation stability
- Long drain interval
- Superior fuel economy (fuel economy benefit over a reference oil of 3,4 %)
- Maximum protection against wear and corrosion
- Excellent fluidity at low temperature

Specifications

	SAE 0W-20
ACEA	A1/B1-12; C5-16
API	SN
FIAT	9.55535-DSX/9.55535-DM1
Volvo	VCC RBSO-2AE

Typical Characteristics

Parameter	Test Method	Typical Value
Density at 20°C, g/ml	EN ISO 3675	0.845
Kinematic Viscosity at 100°C, mm ² /s	EN ISO 3104	9.0
Kinematic Viscosity at 40°C, mm ² /s	EN ISO 3104	48.0
Viscosity Index	ISO 2909	170
Flash point COC, °C	EN ISO 2592	224
Pour point, °C	ISO 3016	-48
TBN (HClO ₄), mg KOH/g	ASTM D 2896	7.8

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit: www.prista-oil.com