



PRISTA® ULTRA GF 0W-20

HIGH PERFORMANCE PASSENGER CAR ENGINE OILS

Description and Application

Prista® Ultra GF 0W-20 is a full synthetic lubricant based on carefully selected very high quality base oils, offering the highest levels of fuel economy in passenger cars. Due to its carefully selected base oils and premium additives, it is designed to deliver outstanding engine protection against wear and deposits. Its exceptionally low viscosity allows it to be used the year round, also during very low temperatures in the wintertime.

Prista® Ultra GF 0W-20 has been specifically developed to meet the challenging requirements for hybrid cars, where fuel economy and CO2 reduction is important.

Benefits

- performance in keeping the engine clean
- superior fuel economy and CO2 reduction
- excellent fluidity at low temperature

Specifications

| | SAE 0W-20 |
|----------|-----------------------------|
| ILSAC | GF-5 |
| API | SN/ Resource conserving |
| GM | GMW 17332 /Service Fill/ |
| FORD | WSS-M2C-945A/946A/947A |
| Chrysler | MS 6395 |

Typical Characteristics

| Parameter | Test Method | Typical Value |
|--|-------------|---------------|
| Density at 20°C, g/ml | EN ISO 3675 | 0.849 |
| Kinematic Viscosity at 100°C, mm ² /s | EN ISO 3104 | 8.7 |
| Kinematic Viscosity at 40°C, mm ² /s | EN ISO 3104 | 47.2 |
| Viscosity Index | ISO 2909 | 167 |
| Flash point COC, °C | EN ISO 2592 | 222 |
| Pour point, °C | ISO 3016 | -42 |
| Sulfated Ash, % | EN ISO 3987 | 0.8 |

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit: www.prista-oil.com