



PRISTA® ULTRA V 0W-20

HIGH PERFORMANCE PASSENGER CAR ENGINE OILS

Description and Application

Prista® Ultra V 0W-20 is a full synthetic premium performance fuel economy engine oil designed with advanced technology additives to meet VW-Audi 508 00/509 00 requirements.

Product is developed for use in gasoline (direct and indirect injection) and direct injected diesel and diesel passenger cars and light commercial vehicles equipped with diesel particulate filters (DPF). Oil is not backwards compatible with other active and obsolete VW/Audi engine oil specifications.

Benefits

- Low ash formulation
- Long drain interval
- Superior fuel economy (fuel economy benefit over a reference oil of 3,4 %)
- Maximum protection against wear and corrosion
- Excellent fluidity at low temperature

Specifications

	SAE 0W-20
ACEA	C5-16
API	SN
VW	508 00/ 509 00
Porsche	C20

Typical Characteristics

Parameter	Test Method	Typical Value
Density at 20°C, g/ml	EN ISO 3675	0.834
Kinematic Viscosity at 100°C, mm ² /s	EN ISO 3104	7.9
Kinematic Viscosity at 40°C, mm ² /s	EN ISO 3104	37.9
Viscosity Index	ISO 2909	180
Flash point COC, °C	EN ISO 2592	200
Pour point, °C	ISO 3016	-57
TBN (HClO ₄), mg KOH/g	ASTM D 2896	7.8

Important note: typical data values do not constitute a specification but are an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved.

Health, Safety and Handling

Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application.

For more information about product MSDS, terms and conditions for storage and shelf life please visit: www.prista-oil.com